



# NSB 100FT Blue+

## AGM Thin Plate Lead Carbon



The NSB Blue+ Battery® delivers ultra fast recharge and exceptional PSoC cycling performance.

- Exceptional PSoC cyclic performance
- Design life 15+ years at 20°C (68°F)
- Ultra fast recharge
- Shelf life of up to 24 months
- Lead carbon added to negative electrodes increases power and reduces sulfation
- High potential fuel savings when used with hybrid genset applications
- Operating temperature range -40°C to +65°C (-40°F to 149°F)
- State-of-the-art automated manufacturing ensures consistency and reliability
- Advanced 3 stage terminal design to ensure leak-free operation - brass terminals provide maximum performance
- High modulus Polyphenylene Oxide (PPO) plastic materials designed to withstand extended elevated operating temperatures and maintain high battery compression essential for reliable operation
- Non-halogenated thermally sealed plastic casing
- Approved as non-hazardous cargo for ground sea and air transport DOT 49CFR173.159(d), (i) and (ii)

# NSB 100FT Blue+

## Nominal Technical Specifications


### Dimensions

|        |        |        |        |
|--------|--------|--------|--------|
| Height | 287 mm | Width  | 108 mm |
| Length | 396 mm | Weight | 34 kg  |

### Electrical

|   |                      |
|---|----------------------|
| Terminal                                | Female M8 x 1.25     |
| Terminal torque                         | 8.0 Nm (71 in-lbs)   |
| 10 hr capacity to 1.80VPC @ 25°C (77°F) | 100 Ah               |
| 8 hr capacity to 1.75VPC @ 25°C (77°F)  | 100 Ah               |
| 10 hr capacity to 1.80VPC @ 20°C (68°F) | 99 Ah                |
| Float voltage @ 20/25°C (68/77°F)       | 2.28 / 2.27 VPC      |
| Impedance (1Khz)                        | 2.6 mΩ @ 25°C (77°F) |
| Conductance                             | 1846 S               |
| Short circuit current                   | 3500 A               |
| Maximum charge current (A)              | No Limit             |
| Operation temperature range             | -40°C to +65°C       |
| Nominal voltage                         | 12 V                 |

### Technical Drawing



All NorthStar batteries are compliant with: Telcordia SR4228, IEC 60896; Bellcore GR-63-Core, Issue 1; British, German, and Russian telecom standards; UL approved and UN2800 certified. NorthStar is registered to ISO 9001 and ISO 14001.

NorthStar Americas PARTIAL  
NorthStar Battery Company LLC  
4000 Continental Way  
Springfield, MO, 65803,  
United States of America  
[info@northstarbattery.com](mailto:info@northstarbattery.com)  
Tel: +1 417 575 8200  
Fax: +1 417 575 8250

NorthStar Europe  
SiteTel Sweden AB  
Haukadalsgatan 8A  
SE-164 40 Kista,  
Stockholm, Sweden  
[europe@northstarbattery.com](mailto:europe@northstarbattery.com)  
Tel: +46 8 410 102 00  
Fax: +46 8 638 06 00

NorthStar Middle East, Africa  
NorthStar Battery DMCC  
Office 702, Saba 1 Tower  
Jumeirah Lake Towers, Dubai  
United Arab Emirates  
[mea@northstarbattery.com](mailto:mea@northstarbattery.com)  
Tel: +971 4 423 8060  
Fax: +971 4 423 8061

NorthStar Asia-Pacific  
NS Asia Pacific Sdn. Bhd.  
B2-3A-13A, Solaris Dutamas  
No. 1, Jalan Dutamas 1, 50480  
Kuala Lumpur, Malaysia  
[asia@northstarsitetel.com](mailto:asia@northstarsitetel.com)  
Tel: +60 3 6419 0711