

## NSB 170FT Blue+



# The NSB Blue+ Battery® delivers ultra fast recharge and exceptional PSoC cycling performance.

- Exceptional PSoC cyclic performance
- Design life 15+ years at 20°C (68°F)
- Ultra fast recharge
- Shelf life of up to 24 months
- Lead carbon added to negative electrodes increases power and reduces sulfation
- High potential fuel savings when used with hybrid genset applications
- Operating temperature range -40°C to +65°C (-40°F to 149°F)
- State-of-the-art automated manufacturing ensures consistency and reliability
- Advanced 3 stage terminal design to ensure leak-free operation - brass terminals provide maximum performance
- High modulus Polyphenylene Oxide (PPO) plastic materials designed to withstand extended elevated operating temperatures and maintain high battery compression essential for reliable operation
- Non-halogenated thermally sealed plastic casing
- Approved as non-hazardous cargo for ground sea and air transport DOT 49CFR173.159(d), (i) and (ii)



## NSB 170FT Blue+

## Nominal Technical Specifications


#### **Dimensions**

Height	320 mm	Width	125 mm
Length	560 mm	Weight	60 kg

#### Electrical

Terminal	Female M8 x 1.25	
Terminal torque	8.0 Nm (71 in-lbs)	
10 hr capacity to 1.80VPC @ 25°C (77°F)	170 Ah	
8 hr capacity to 1.75VPC @ 25°C (77°F)	168 Ah	
10 hr capacity to 1.80VPC @ 20°C (68°F)	168 Ah	
Float voltage @ 20/25°C (68/77°F)	2.28 / 2.27 VPC	
Impedance (1Khz)	2.1 m <b>Ω</b> @ 25°C (77°F)	
Conductance	2380 S	
Short circuit current	6000 A	
Maximum charge current (A)	No Limit	
Operation temperature range	-40°C to +65°C	
Nominal voltage	12 V	

### Technical Drawing



All NorthStar batteries are compliant with: Telcordia SR4228, IEC 60896; Bellcore GR-63-Core, Issue 1; British, German, and Russian telecom standards; UL approved and UN2800 certified. NorthStar is registered to ISO 9001 and ISO 14001.